

HAKKIPIILKE®

50 Pro

+ HAKKICUT™
HAKKISPLIT™

The Hakki Pilke 50 Pro is the most powerful professional firewood processor in its size category on the market. One cubic metre of firewood is produced with seven splitting strokes. The productivity of the machine has been improved with the excellent delay-free HakkiSplit™ splitting mechanism as well as new features that ensure uninterrupted material flow – a hydraulic log press and a hydraulically retracted measuring device.

The Hakki Pilke 50 Pro is an ergonomic workhorse for the professional including the innovative Pro Series new user interface. HakkiCut™ cutting control always adds optimal cutting force and enables whole cutting operation with one joystick button. Combined with the automatic, hydraulically operated chain tensioner and the automatic chain lubrication pump, which is activated during sawing, these features ensure that the saw chain and bar last for a long time and provide unparalleled sawing efficiency time and time again. The adjustable support legs make the machine easy to set up on an uneven surface. The operating platform also comes with adjustable legs.

The machine is light for its size and has an ideal weight distribution, meaning that it can be safely transported using the three-point hoist of a medium-sized tractor.

- **SUPER-EFFICIENT PROFESSIONAL PROCESSOR FOR INDUSTRIAL FIREWOOD PRODUCTION**
- **NEW USER INTERFACE**
- **AUTOMATIC HYDRAULIC CHAIN TENSIONER AS STANDARD**
- **CAN BE EQUIPPED WITH DIFFERENT LOG TABLES AND SPLITTING BLADES**



The manufacturer reserves the right to make changes.



An unparalleled user interface which enables you to process firewood with just two buttons.



The AC 10 automatic chain tensioner maintains optimal saw chain tension at all times. The chain can be conveniently replaced after releasing chain tension with the lever pictured – no tools required!

EASY 50 PRO

 **470**
MM

 **600**
MM

 **30**
T



TECHNICAL SPECIFICATIONS

Max log diameter	470 mm
Max log length	600 mm
Maximum splitting power	3–30 t
Bar	20"
Power source	PTO, electric, combi
Splitting blade	6-way
Outfeed conveyor length	4 m
Outfeed conveyor width	400 mm
Infeed conveyor (width x length)*	0.3 x 2.85 m

STANDARD EQUIPMENT

- Infeed serial connection kit
- Hydraulic infeed conveyor
- Hydraulic infeed roller
- Infeed guide plate
- Hydraulic log press
- Safety cover
- AC10 automatic chain tensioner (hydraulic)
- HakkiCut™ cutting control
- Automatic chain oil lubrication
- Hydraulically retracting log measuring device
- HakkiSplit™ delay-free splitting (3 speeds)
- Hydraulic height adjustment of the splitting blade
- Automatically adjusting splitting power (3 different power settings)
- Hydraulic vertically and laterally pivoting outfeed conveyor
- Outfeed conveyor speed control + reverse
- Cleaning outfeed conveyor
- Oil cooler
- Adjustable work platform

DIMENSIONS IN TRANSPORT POSITION

Height	2,900 mm
Length	3,100 mm
Width	1,520 mm
Weight	2,200 kg

OPTIONAL EQUIPMENT

Splitting blade	2/4, 8, 12 -way
Outfeed conveyor extension **	1 m
Oil heater	
Blower saw-dust removal	

ACCESSORIES

HakkiFeed	422, 471, 472
Hakki Pilke Cleaner	
Hakki Pilke Roller	
Powerpack	

* length with a hydraulic infeed roller



Replacing the splitting blade is fast and safe thanks to the detachable winch.



Patented cleaning outfeed conveyor as standard. The groove at the end of the outfeed conveyor separates debris from the firewood.