



XYLOCRIBLE 2 M



XYLOCRIBLE 4 m + buffering screener



Rabaud advantages

- 2 models with large sifting areas (L x W) :
2 x 1 m on XYLOCRIBLE 2 M.
4 x 1 m on XYLOCRIBLE 4 M.

- Rolls driven electrically or hydraulically.
- Wood screener loading by bucket or wood processor outcome conveyor.
- Square cam rolls to separate the waste from the logs.
- Underneath waste evacuation.
- Custom configuration.
- Option : 6 cubic meters volume buffering storer through metal laths conveyor.

Technical characteristics

MODELS	XYLOCRIBLE 2M	XYLOCRIBLE 4M
<i>Sifting area (L x W)</i>	2 x 1 m	4 x 1 m
<i>Number of cams</i>	6 square + 1 «round» cam roll	15 square + 1 «round» cam roll
<i>Netting width</i>		48 mm
<i>Disc thickness</i>		12 mm
<i>Rotation speed</i>		58 rpm
<i>Weight</i>	from 1300 kg	From 4000 kg

— Standard equipment —

- Front and side loading hopper on XYLOCRIBLE 4 M.
- Individual and offset lubricating system for chain bearings.
- Progressive start-up motion for electric version.
- Reverse gear on electric versions.



Specific conditions :
Consult us



For more information, contact us on +33 (0)2 51 48 51 43





